

CURVAS 90° DE SOLDAR

GAMA ISO


Diâmetro Nominal		Diâmetro D mm (mm)	Radio R mm (mm)	Espessura T mm (mm)	Peso Kgs
DN	Polegadas				
15	1/2"	21,3	28	1,6/2	0,03/0,04
20	3/4"	26,9	29	1,6/2	0,05/0,06
25	1"	33,7	38	1,6/2	0,08/0,09
32	1 1/4"	42,4	48	1,6/2	0,14/0,20
40	1 1/2"	48,3	57	1,6/2	0,19/0,21
50	2"	60,3	76	1,6/2	0,29/0,40
65	2 1/2"	76,1	95	1,6/2	0,56/0,60
80	3"	88,9	114	2/3	0,78/1,16
100	4"	114,3	152	2/3	1,35/2,01
125	5"	139,7	190	2/3	2,07/3,10
150	6"	168,3	229	2/3	3,3/4,9
200	8"	219,1	305	2/3	5,2/7,8
250	10"	273	381	2/3	8,25/12,4
300	12"	323,9	457	2/3	11,7/17,75
350	14"	355,6	533,5	3/4	22/29,4
400	16"	406,4	609,5	3/4	29/38
450	18"	457,2	686	3/4	37/49
500	20"	508	762	3/4	45/60
600	24"	609,6	914	3/4	65/86,5
700	28"	711,2	1070	4/5	119/149
800	32"	812,8	1220	4/5	156/195
900	36"	914,4	1372	4/5	206/246
1000	40"	1016	1525	4/5	243/304

Qualidade Material:


AISI

304 – 304L

316 – 316L



RAIO LONGO
(A= 1.5 x DN)



RAIO CURTO
(A= 1 x DN)